



Cable Jacket Guide for Harsh Environment Applications

The information below is being provided to better understand the applications and specific characteristics of individual cables at a quick glance. Please refer to the individual family spec sheets for further specifications and ordering information or call Customer Care at 1-800-743-2671 with any questions.

	MIC®, MIC Unitized Riser	MIC DX Riser	MIC, MIC Unitized Interlocking Armor Riser	MIC, MIC Unitized Plenum	MIC DX Plenum	MIC, MIC Unitized Interlocking Armor Plenum	FREEDM®, FREEDM One, FREEDM One Unitized, FREEDM LST™ Riser	FREEDM Plenum	FREEDM One, FREEDM LST Plenum	Industrial LSZH™	Industrial LSZH Fiberglass-Armored	Mining and Petrochemical	ALTOS® with FastAccess® Technology	ALTOS Lite™	SST-Drop™
PVC Riser	■	■	■				■				■				
PVC Plenum				■	■	■			■						
PVDF								■							
LSZH										■	■	■			
MDPE													■	■	■
Polyamide/Nylon Overjacket Available														■	■
Indoor	■	■	■	■	■	■	■	■	■	■	■	■			
Outdoor							■	■	■	■	■	■	■	■	■
Duct	■			■			■	■	■	■	■	■	■	■	■
Aerial							■	■	■	■	■	■	■	■	■
Direct Buried										■	■	■		■	■
Low Friction	■	■	■	■	■	■	■	■	■				■	■	■
UV Resistant							■	■	■	■	■	■	■	■	■
Fungus Resistant							■	■	■	■	■	■	■	■	■
Water Resistant							■	■	■	■	■	■	■	■	■
Metallic Armor			■			■								■	
Dielectric Armor		■			■										
Fiberglass Armor											■				
Impact and Crush Resistance		■	■		■	■				■	■	■		■	
Rodent Resistance			■			■					■			■	
Tray Rated										■	■	■			
Petrochemical Resistance												■			
Minimum Operating Temperature °C (°F)	-20 (-4)	-20 (-4)	-20 (-4)	0 (32)	0 (32)	0 (32)	-40 (-40)	-40 (-40)	-40 (-40)	-50 (-58)	-50 (-58)	-50 (-58)	-40 (-40)	-40 (-40)	-40 (-40)
Maximum Operating Temperature °C (°F)	70 (158)	70 (158)	70 (158)	70 (158)	70 (158)	70 (158)	70 (158)	70 (158)	70 (158)	75 (167)	75 (167)	75 (167)	70 (158)	70 (158)	70 (158)



For more information on Corning Cable Systems LANscape® Solutions for Harsh Environments, please contact us at 800-743-2675 or visit <http://www.corning.com/cablesystems/HarshEnvironments>



Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA
 800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 www.corning.com/cablesystems

Corning Cable Systems reserves the right to improve, enhance and modify the features and specifications of Corning Cable Systems products without prior notification. ALTOS, FastAccess, FREEDM, LANscape and MIC are registered trademarks of Corning Cable Systems Brands, Inc. Lite, LST, LSZH and SST-Drop are trademarks of Corning Cable Systems Brands, Inc. All other trademarks are the properties of their respective owners. Corning Cable Systems is ISO 9001 certified. © 2013 Corning Cable Systems. All rights reserved. Published in the USA. LAN-1607-AEN / August 2013